

Tutti i modelli / All models: F80C - F120 - F125C - F200 - SF300 - SF500 - SFN1000 - SFN2200

## Dati Tecnici - Specifications

	cond	comp. W	ABS. W	Fuse	Kwh/100Kg	l / h	kg	Lbs	kg	Lbs	Ton CO2 equiv.
<b>SFN2200 A</b>		13220	6250	25	7.4	79	390	859	411	904	15,69
<b>SFN2200 W</b>		13220	6250	25	7.4	1750	371	816	392	862	7,84

## 24h Produzione Ghiaccio - Ice Production (kg/lbs)

### Raffreddamento ad aria - Air Cooled Unit

Temp. aria Air Temp.	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	<b>1820</b>	<b>2160</b>	<b>2830</b>	<b>2500</b>
50°	4012	4762	5137	5512
21°	<b>1800</b>	<b>2100</b>	<b>2250</b>	<b>2400</b>
70°	3698	4630	4960	5291
32°	<b>1650</b>	<b>1850</b>	<b>1950</b>	<b>2050</b>
90°	3638	4078	4299	4519
38°	<b>1500</b>	<b>1640</b>	<b>1710</b>	<b>1780</b>
100°	3307	3616	3770	3924

### Raffreddamento ad acqua - Water Cooled Unit

Temp. aria Air Temp.	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	<b>1580</b>	<b>2050</b>	<b>2250</b>	<b>2500</b>
50°	3483	4519	4960	5512
21°				
70°				
32°				
90°				
38°				
100°				



### PANNELLO DI CONTROLLO - CONTROL PANEL



### DEPOSITO - BIN

UD1000-DR620


### DIMENSIONI - DIMENSIONS

LxPxH(mm): 1080 x 780 x 1255  
WxDxH(in): 42 8/16" x 30 1/16" x 49 6/16"

### DATI SPEDIZIONE / SHIPPING DATA

LxPxH(mm): 1170 x 920 x 1340  
WxDxH(in): 46" 1/16 x 36" 4/16 x 52" 12/16

### TIPO GHIACCIO - ICE TYPE



PERCENTUALE ACQUA RESIDUA 25%  
ICE CONTAINS 25% RESIDUAL WATER

### CONDIZIONI USO-OPERATING REQUIREMENTS



400V / 50Hz



R404a GWP=3922

MIN

MAX

10°C (50°F)



40°C (104°F)

5°C (41°F)



35°C (95°F)

- 10 %



+ 10 %





1 BAR (14 PSI)



5 BAR (70 PSI)

Calore espulso - Rejected Heat  
Volume aria - Air Volume

**19100 W**  
**7000 m³/h**



- A** Alimentazione elettrica  
Electrical cable supply
- B** Entrata acqua 3/4" gas  
Water inlet 3/4" gas
- C** Scarico acqua  
Water drain ø 20 mm
- D** Entrata acqua - raffr. acqua 3/4" gas  
Water inlet - cooled unit 3/4" gas
- E** Scarico bacinella 3/4" gas  
Overflow drain 3/4" gas

GAS - SOLO PER  
CONDENSATORE REMOTO  
GAS - ONLY ON AIR COOLED  
REMOTE CONDENSER

SOLO PER CONDENSATORE REMOTO  
ONLY ON AIR COOLED REMOTE  
CONDENSER

OVERSIZED CONDENSER FOR 43°C AMBIENT

